ZCS-KDCA1

Data Docking Station



Features

- High Performance
 13.3" color LCD with resolution of 1920*1080
 Supports up to 24 units of body worn camera
 Supports up to 24TB storageC

- Easy to Use

 Wall-mount and desktop design, easy to install

 Modular design, easy to upgrade system capacity

 Plug and play, auto charging and data transmission

 Touch screen operation

Abundant Functions and Features

- Record seaching and playback Auto lock after device plug in Use the password to unlock device
- Priority slot for far speed data transmission Power-off protection by built-in battery

Specifications

Extended Module Solot Funtions Slot Funtions Battery charging, Data transmission, Lock, Priority slot, Automatic upgrade, Time correction Full load: up to 4.6MB/s per slot For priority slot: up to 15MB/s Alarm System Alarm Triggers Alarm Events Storage Max. Internal HDDs Ax. 24TB (up to 8TB/each) RAID Interfaces Ethernet 1 x Gigabite network port, RJ45 interface Audio Out Build-in speaker Point lock 1 x Point lock (Unlock all devices at the same time bye key) "1 x USB 2.0 for extended device 2 x Mini USB: for thirdparty device charging Departing Temperature Operating Humidity Etectrical Power 100° C ~ 55°C / 14°F ~ 131°F Electrical Power 100° C ~ 55°C / 14°F ~ 131°F Electrical Power 100° C ~ 55°C / 14°F ~ 131°F Electrical Power 100° C ~ 55°C / 14°F ~ 131°F Electrical Power 100° C ~ 55°C / 14°F ~ 131°F Electrical Power 100° C ~ 55°C / 14°F ~ 131°F Electrical Power 2CS-KDCA1-6 + 1 x ZCS-KDCA1-EX6: Max. 135W ZCS-KDCA1-6 + 1 x ZCS-KDCA1-EX6: Max. 165W ZCS-KDCA1-6 + 3 x ZCS-KDCA1-EX6: Max. 155W ZCS-KDCA1-6 + 3 x ZCS-KDCA1-EX6: Max. 195W Built-in battery: 2150mAh Mechanical Weight 2 CS-KDCA1-1-6 : 1 0 . 3 K g / 2 2 . 71 b (HDD not included)		
Operating System Processor Intel N3710 Application System Agam Agament Data Docking Station Management Software RAM 4GB User Management User login / User operation / Alarm / Update Display Size 13.3" Resolution 1920*1080 Touch Screen Supported Search & Playback File Type Search Mode Duration filter / Tag Playback Resolution Functions Functions Solot Default Slot Supports up to 3 extended modules (6 slots per module) Extended Module Solots by default, supports 6 units of Body Worn Camera Supports up to 3 extended modules (6 slots per module) Extended Module Solot For priority slot: up to 15MB/s Slot Funtions Stot Funtions Data Loading Speed Alarm System Alarm Triggers Alarm Events Storage Max. Internal HDDs RAID RAID RAID RAID RAID RAID RAID RAID		ZCS-KDCA1
Processor Intel N3710 Data Docking Station Management Software AdB AdB Admin / User User login / User		
Application System RAM 4GB User Management Log Management User login / User operation / Alarm / Update Size 13.3" Resolution 1920*1080 Search & Playback File Type Search Mode Playback Flore Supported Search Mode Duration filter / Tag Playback Resolution Functions Functions Solot Default Slot Supports up to 3 extended modules (6 slots per module) Extended Module Solots by default, supports 6 units of Body Worn Camera Supports up to 3 extended modules (6 slots per module) Extended Module Solot For priority slot: up to 15MB/s Stot Funtions Stot Funtions Data Loading Speed Alarm System Alarm Triggers Alarm Events Storage Max. Internal HDDs RAID RAID RAID RAID RAID RAID RAID RAID RAID RAID RAID Interfaces Ethernet 1 x Gigabite network port, RJ45 interface Build-in speaker Point look 1 x Point 1 look (Unlock all devices at the same time bye key) "1" x USB 2.0: for extended device 2 x Mini USB 2.0: for extended device 3 x Micro USB 5 for thirdparty device ch		
RĀM JUSER Management Log Management User login / User operation / Alarm / Update Display Size 13.3" Resolution 1920*1080 Touch Screen Search & Playback File Type Search Mode Duration filter / Tag Playback Resolution 1 x 1080p@30fp Functions Supported Supported Search Mode Playback Resolution 1 x 1080p@30fp Functions Stot	Processor	Intel N3710
User Management Display	Application System	Data Docking Station Management Software
Log Management User login / User operation / Alarm / Update	RAM	4GB
Log Management Duser login / User operation / Alarm / Update Display Size 13.3" Resolution 1920*1080 Touch Screen Supported Supported Search & Playback File Type Video, Audio, Pic, Log Search & Playback File Type Search Mode Duration filter / Tag Playback Resolution 1 x 1080p@30fp Functions Querying, Viewing, Downloading, Removing Slot 6 Slots by default, supports 6 units of Body Worn Camera Supports up to 3 extended modules (6 slots per module) 2CS-KDCA1-EX6: Extended modules (6 slots per module) supports 6 units of Body Worn Camera Supports up to 3 extended modules (7 SchCA1-6, 6 slots per module, supports 6 units of Body Worn Camera Supports up to 3 extended modules (7 SchCA1-6, 6 slots per module, supports 6 units of Body Worn Camera Supports up to 3 extended modules (7 SchCA1-6, 6 slots per module, supports 6 units of Body Worn Cameras Supports up to 3 extended modules (7 SchCA1-6, 6 slots per module, supports 6 units of Body Worn Cameras Supports up to 15 Mere SchCA1-6, 6 slots per module, supports 6 units of Body Worn Cameras Supports up to 15 Mere SchCA1-6, 6 slots per module, supports 6 units of Body Worn Camera Supports up to 15 Mere SchCA1-6, 6 slots per module, supports 6 units of Body Worn Camera Supports up to 15 Mere SchCA1-6, 6 slots per module, supports 6 units of Body Worn Camera Supports up to 15 Mere SchCA1-6, 1 x SchC	User Management	Admin / User
Size 13.3" Resolution 1920*1080 19		User login / User operation / Alarm / Update
Size 13.3"		, , , , , , , , , , , , , , , , , , , ,
Resolution Touch Screen Search & Playback File Type Search Mode Playback Resolution Fluctoins Slot Default Slot Default Slot Supports up to 3 extended modules (6 slots per module) Strended Module Strended Module Extended Module Strended Module Strended Module Strended Module Store Care Charles (6 slots by default, supports 6 units of Body Worn Camera Supports up to 3 extended modules (6 slots per module) Store Functions Slot Extended Module Store Charles (6 slots per module) Store Charles (6 slots per module) Store Functions Slot Function File Supports up to 3 extended modules (6 slots per module) ScS-KDCA1-EX6: Extended modules (7 zCS-KDCA1-6, 6 slots per module, supports of units of Body Worn Camera Slots Function File Supports up to 15MB/s Slot Functions Sl		13.3"
Supported Supp		
Search & Playback File Type Search Mode Playback Resolution Functions Slot Default Slot Default Slot Supports up to 3 extended modules (6 slots per module) Extended Module Stot Functions Slot Juports up to 3 extended modules (6 slots per module) Extended Module Stot Functions Slot Juports up to 3 extended modules (6 slots per module) Extended Module Stot Functions Slot Functions Slot Gentles of Body Worn Cameras Supports up to 3 extended modules (6 slots per module) Extended Module Slot Functions Slot Function Slot Functions Slot Functions Slot Function Slot Functions Slot Functions Slot Functions Slot Functions Slot Function Slot Function Slot Function Slot Function Slot Function Slot Function Slot F		
File Type Search Mode Playback Resolution Flayback Resolution Flayback Resolution Flunctions Slot Default Slot Default Slot Slot Slot Supports up to 3 extended modules (6 slots per module) Extended Module Extended Module Extended Module Slot Funtions Slot Funding Speed For priority slot: up to 15MB/s For priority slot: up to 15MB/s For priority slot: up to 15MB/s Slot Funtions Slot Funtions No disk / Insufficient recording space / Network disconnected Sluzzer / Alarm text Slot June Funtions Slot Funtions Slot Funding Funding Funtions Slot Funding Funding Funding Funtions Funtions Environmental Operating Funding Funding Funcional Funding Funding Funding Funding Funcional Funding		bapporcea
Search Mode Playaback Resolution Functions Slot Default Slot Default Slot Extended Module Extended Module Slot Functions Slot Functions Slot Default Slot Extended Module Extended Module Slot Functions Data Loading Speed Alarm Pfull load: up to 4.6MB/s per slot For priority slot: up to 15MB/s System Alarm Triggers Alarm Events Storage No disk / Insufficient recording space / Network disconnected Alarm Events Storage Nax. Internal HDDs RAID RAID RAID RAID RAID RAID RAID Interfaces Ethernet 1 x Gigabite network port, RJ45 interface Audio Out Point look 1 x Point lock (Unlock all devices at the same time bye key) "1 x USB 2.0: for extended device 2 x Mini USB 2.0: for extended device 2 x Mini USB rot thirdparty device charging 2 x Micro USB: for thirdparty device charging Derating Humidity Flectrical Doward For Protection Mechanical Weight 2 CS - KDCA1 - 6 + 1 x ZCS-KDCA1 - EX6: Max. 195W EVEN - CS - KDCA1 - 6 + 2 x ZCS-KDCA1 - EX6: Max. 195W Bullich in States ZCS - KDCA1 - 6 + 1 x x ZCS-KDCA1 - EX6: Max. 195W Bullich in States ZCS - KDCA1 - 6 + 1 x x ZCS-KDCA1 - EX6: Max. 195W Bullich in States ZCS - KDCA1 - 6 + 1 x x ZCS-KDCA1 - EX6: Max. 195W Bullich in States ZCS - KDCA1 - 6 + 1 x x ZCS-KDCA1 - EX6: Max. 195W Bullich in States ZCS - KDCA1 - 6 + 1 x x ZCS-KDCA1 - EX6: Max. 195W Bullich in States ZCS - KDCA1 - 6 + 1 x x ZCS-KDCA1 - EX6: Max. 195W Bullich in States ZCS - KDCA1 - 6 + 1 x x ZCS-KDCA1 - EX6: Max. 195W Bullich in States ZCS - KDCA1 - 6 + 1 x x ZCS - KDCA1 - EX6: Max. 195W Bullich in States ZCS - KDCA1 - 6 + 1 x x ZCS - KDCA1 - EX6: Max. 195W Bullich in States ZCS - KDCA1 - 6 + 1 x x ZCS - KDCA1 - EX6: Max. 195W Bullich in States ZCS - KDCA1 - 6 + 1 x x ZCS - KDCA1 - EX6: Max. 195W Bullich in States ZCS - KDCA1 - 6 + 1 x x ZCS - KDCA1 - EX6: Max. 195W Bullich in States ZCS - KDCA1 - 6 + 1 x		Video Audio Pic Log
Playback Resolution Flunctions Slot Slot Default Slot Default Slot Extended Module Stypports up to 3 extended modules (6 slots per module) Extended Module Slot Funtions Slot Funding Slot Funding F		
Functions Slot Default Slot Default Slot Extended Module Extended Module Slot Funtions Slot Funtions Data Loading Speed Alarm System Alarm Triggers Alarm Events Storage Max. Internal HDDs RAID RAID RAID RAID RAID RAID RAID RAID RAID ROUT Slot Side Side Side Side Side Sper module) 1 CS-KDCA1-EA6: Extended modules of ZCS-KDCA1-6, 6 slots per module, supports of units of Body Worn Cameras Battery charging, Data transmission, Lock, Priority slot, Automatic upgrade, Time correction Full load: up to 4.6MB/s per slot For priority slot: up to 15MB/s System Alarm Triggers Alarm Events System Alarm Triggers Alarm Events Storage No disk / Insufficient recording space / Network disconnected Alarm Events Storage RAID I RAID RAID RAID RAID RAID RAID Interfaces Ethernet 1 x Gigabite network port, RJ45 interface Audio Out Bulld-in speaker 1 x Point lock (Unlock all devices at the same time bye key) "1 x USB 2.0: for extended device 2 x Mini USB 2.0: for extended device 2 x Mini USB x for thirdparty device charging 2 x Micro USB: for thirdparty device charging 2 x Micro USB: for thirdparty device charging 10% ~ 95% Environmental Operating Temperature Operating Humidity Flectrical 10% ~ 95% CCS-KDCA1-6: 1 x ZCS-KDCA1-EX6: Max. 135W ZCS-KDCA1-6: 1 x ZCS-KDCA1-EX6: Max. 195W Power Consumption Mechanical Weight ZCS-K DCA1-6: 1 0.3 Kg / 22.71b (HDD not included) ZCS-KDCA1-6: 2X x 50 x 50 x 50 8 mm / 16.92" x 20.08" x 3.86"		
Default Slot Default Slot Default Slot Supports up to 3 extended modules (6 slots per module) Extended Module Extended Module Extended Module ZCS-KDCA1-EX6: Extended modules (6 slots per module) ZCS-KDCA1-EX6: Extended modules (6 slots per module) ZCS-KDCA1-EX6: Extended modules (6 slots per module) ZCS-KDCA1-EX6: Extended modules (7 slots per module) ZCS-KDCA1-EX6: Extended modules (6 slots per module) Extended Module ZCS-KDCA1-EX6: Extended modules (6 slots per module) ZCS-KDCA1-EX6: Astended modules (7 slots per module) Automatic upgrade, Time corrections and the slots per module, supports yellow priority slot: up to 15MB/s Solts per slot priority slot: up to 15MB/s No disk / Insufficient recording space / Network disconnected Buzzer / Alarm text Storage Max. Internal HDDS As 3.5." hard disk drawer (1 x 4TB Hard disk included) Max. 24TB (up to 8TB/each) RAID Tatterfaces Ethernet 1 x Gigabite network port, R145 interface Build-in speaker Point lock 1 x Point lock (Unlock all devices at the same time bye key) "1 x USB 2.0: for extended device 2 x Minro USB: for thirdparty device charging Environmental Operating Humidity Electrical Power 100 ~ 240V AC, 50 ~ 60Hz "ZCS-KDCA1-6 + 1 x ZCS-KDCA1-EX6: Max. 135W ZCS-KDCA1-6 + 2 x ZCS-KDCA1-EX6: Max. 165W ZCS-KDCA1-6 + 3 x ZCS-KDCA1-EX6: Max. 165W ZCS-KDCA1-6 + 2 x ZCS-KDCA1-EX6: Max. 195W Built-in battery: 2150mAh Mechanical Weight ZCS-K DCA1-6: 1 0 . 3 K g / 2 2 . 7 l b (H D D n ot included) ZCS-KDCA1-6 + 6 . 3 x x 5 l o x 98 mm / 16 . 92" x 2 0 . 08" x 3 . 86"		
Default Slot Slot Sby default, supports 6 units of Body Worn Camera Supports up to 3 extended modules (6 slots per module) ZCS-KDCA1-EX6: Extended modules (6 slots per module) ZCS-KDCA1-EX6: Extended modules (6 slots per module) ZCS-KDCA1-EX6: Extended modules (7 slots per module) ZCS-KDCA1-EX6: Extended modules (7 slots per module, supports of units of Body Worn Cameras Slots Funtions Data Loading Speed Alarm Full load: up to 4.6MB/s per slot For priority slot: up to 15MB/s No disk / Insufficient recording space / Network disconnected Alarm Events Storage No disk / Insufficient recording space / Network disconnected Alarm Events Storage No disk / Insufficient recording space / Network disconnected Alarm Events Storage Nax. Internal HDDs Ax 3.5" hard disk drawer (1 x 4TB Hard disk included) Max. 24TB (up to 8TB/each) RAID Interfaces Ethernet 1 x Gigabite network port, RJ45 interface Audio Out Build-in speaker Point lock 1 x Point 1 lock (Unlock all devices at the same time bye key) "1 x USB 2.0: for extended device 2 x Mini USB 2.0: for extended device 2 x Mini USB 8: for thirdparty device charging 2 x Micro USB: for thirdparty device charging 2 x Micro USB: for thirdparty device charging 10% ~ 95% Environmental Operating Humidity Dower Consumption CCS-KDCA1-6: 1 x ZCS-KDCA1-EX6: Max. 135W CCS-KDCA1-6: 1 x ZCS-KDCA1-EX6: Max. 165W CCS-KDCA1-6: 4 x ZCS-KDCA1-EX6: Max. 195W Built-in battery: Z155mMh Mechanical Weight ZCS-KDCA1-6: 1 0 . 3 K g / 2 2 . 7 lb (HDD not included) ZCS-KDCA1-6: 1 6 . 1 0 . 3 K g / 2 2 . 7 lb (HDD not included) ZCS-KDCA1-6: A3 x 5 10 x 98 mm / 16.92" x 20.08" x 3.86"		Querying, viewing, bownloading, kemoving
Supports up to 3 extended modules (6 slots per module) Extended Module	SIOT	legis i i e ii e ii e ii e ii e
Supports up to 3 extended modules (6 slots per module), supports up to 3 extended module of 2CS-kDCA1-6, 6 slots per module, supports G units of Body Worn Cameras Slot Funtions Slot Funtions Battery charging, Data transmission, Lock, Priority slot, Automatic upgrade, Time correction Full load: up to 4.6MB/s per slot For priority slot: up to 15MB/s Alarm System Alarm Triggers Alarm Events Storage Max. Internal HDDs 3 x 3.5" hard disk drawer (1 x 4TB Hard disk included) Max. 24TB (up to 8TB/each) RAID RAID TINTERFACES Ethernet 1 x Gigabite network port, RJ45 interface Build-in speaker Point lock 1 x Point lock (Unlock all devices at the same time bye key) "1 x USB 2.0 for extended device 2 x Mini USB: for thirdparty device charging 2 x Micro USB: for thirdparty device charging Environmental Operating Temperature Operating Humility Electrical Power 100 ~ 240V AC, 50 ~ 60Hz "2CS-KDCA1-6 + 1 x ZCS-KDCA1-EX6: Max. 135W ZCS-KDCA1-6 + 2 x ZCS-KDCA1-EX6: Max. 165W ZCS-KDCA1-6 + 3 x ZCS-KDCA1-EX6: Max. 195W Built-in battery: 2150mAh Mechanical Weight ZCS-KDCA1-6: 10.3 Kg / 22.71b (HDD not included) ZCS-KDCA1-6.5 3 x 50 x 510 x 98mm / 16.92" x 20.08" x 3.86"	Default Slot	
Extended Module 5 units of Body Worn Cameras Slot Funtions Slot Funtions Battery charging, Data transmission, Lock, Priority slot, Automatic upgrade, Time correction Full load: up to 4.6MB/s per slot For priority slot: up to 15MB/s Alarm No disk / Insufficient recording space / Network disconnected Suzzer / Alarm text Storage Max. Internal HDDs 3 x 3.5" hard disk drawer (1 x 4TB Hard disk included) Max. 24TB (up to 8TB/each) RAID RAID TINTERFACES Ethernet 1 x Gigabite network port, RJ45 interface Audio Out Build-in speaker Point lock 1 x Point lock (Unlock all devices at the same time bye key) "1 x USB 2.0 for extended device 2 x Mini USB: for thirdparty device charging 2 x Micro USB: for thirdparty device charging Environmental Operating Temperature Operating Temperature 10% ~ 55% / 14% ~ 131% Dower Consumption Power 100 ~ 240V AC, 50 ~ 60Hz "2CS-KDCA1-6 + 1 x ZCS-KDCA1-EX6: Max. 135W ZCS-KDCA1-6 + 2 x ZCS-KDCA1-EX6: Max. 165W ZCS-KDCA1-6 + 3 x ZCS-KDCA1-EX6: Max. 195W Built-in battery: 2150mAh Mechanical Weight ZCS-KDCA1-6: 10.3 Kg / 22.71b (HDD not included) ZCS-KDCA1-6.6 id x x 510 x 98mm / 16.92" x 20.08" x 3.86"	Designation of the second of t	
Slot Funtions Slot Funtions Data Loading Speed Alarm System Alarm Triggers Alarm Events Storage Max. Internal HDDs Max. 24TB (up to 8TB/each) RAID Tinterfaces Ethernet Audio Out Build-in speaker Build-in speaker Point look 1 x Fignit Jock (Unlock all devices at the same time bye key) "I'x USB 2.0 for extended device 2 x Mini USB: for thirdparty device charging Derating Humidity Electrical Power Loo 240V AC, 50 ~ 60Hz TCS-KDCA1-6 + 1x ZCS-KDCA1-EX6: Max. 195W Builk-in battery: 2150mAh Mechanical Weight ZCS-KDCA1-6 + 2x ZCS-KDCA1-EX6: Max. 195W Builk-in battery: 2150mAh Mechanical Weight ZCS-KDCA1-6: 10.3 Kg / 22.71b (HDD not included) ZCS-KDCA1-6: 163. X 510 x 98mm / 16.92" x 20.88" x 3.86"	Extended Module	ZCS-KDCA1-EX6: Extended module of ZCS-KDCA1-6, 6 slots per module, supports
Slot Funtions Battery charging, Data transmission, Lock, Priority slot, Automatic upgrade, Time correction Data Loading Speed Alarm System Alarm Triggers System Alarm Triggers Max. Internal HDDs RAID RAID RAID RAID RAID RAID RID R		6 units of Body Worn Cameras
Data Loading Speed		
Data Loading Speed Full load: up to 4.6MB/s per slot For priority slot: up to 15MB/s	Slot Funtions	
For priority slot: up to 15MB/s		
No disk / Insufficient recording space / Network disconnected	Data Loading Speed	
System Alarm Triggers No disk / Insufficient recording space / Network disconnected Alarm Events Buzzer / Alarm text Storage Max. Internal HDDS 3 x 3.5" hard disk drawer (1 x 4TB Hard disk included) Max. 24TB (up to 8TB/each) RAID Interfaces 1 x Gigabite network port, RJ45 interface Ethernet 1 x Gigabite network port, RJ45 interface Audio Out Build-in speaker Point lock 1 x Point lock (Unlock all devices at the same time bye key) "1 x USB 2.0: for extended device USB 2 x Mini USB: for thirdparty device charging Environmental 2 x Micro USB: for thirdparty device charging Deperating Temperature -10°C ~ 55°C / 14°F ~ 131°F Doperating Humidity 10% ~ 95% Electrical 100 ~ 240V AC, 50 ~ 60Hz Power 100 ~ 240V AC, 50 ~ 60Hz "ZCS-KDCA1-6 + 1 x ZCS-KDCA1-EX6: Max. 135W ZCS-KDCA1-6 + 2 x ZCS-KDCA1-EX6: Max. 165W ZCS-KDCA1-6 + 3 x ZCS-KDCA1-EX6: Max. 195W Built-in battery: 2150mAh Mechanical Weight ZCS-KDCA1-6: 43 x S10 x 510 x 98 mm / 16.92" x 20.08" x 3.86"		For priority slot: up to 15MB/s
Alarm Events Suzzer / Alarm text		
Storage		
Max. Internal HDDs 3 3 3.5" hard disk drawer (1 x 4TB Hard disk included) Max. Z4TB (up to 8TB/each) RAID Interfaces RAID 1 Ethernet 1 x Gigabite network port, R145 interface Audio Out Build-in speaker Point lock 1 x Point lock (Unlock all devices at the same time bye key) "1 x USB 2.0: for extended device USB 2 x Minr USB: for thirdparty device charging Z x Minro USB: for thirdparty device charging Departing Temperature 1.0°C ~ 55°C / 14°F ~ 131°F Operating Humidity 110% ~ 95% Electrical 100 ~ 240V AC, 50 ~ 60Hz Power 100 ~ 240V AC, 50 ~ 60Hz "ZCS-KDCA1-6 + 1 x ZCS-KDCA1-EX6: Max. 135W ZCS-KDCA1-6 + 2 x ZCS-KDCA1-EX6: Max. 165W Power-Off Protection Mechanical Weight ZCS-KDCA1-6: 1 0.3 Kg / 2.71b (HDD not included) ZCS-KDCA1-6: 26: 30 x 510 x 98 mm / 16.92" x 20.08" x 3.86"		Buzzer / Alarm text
Max. 24TB (up to 8TB/each)		
RAID Tinterfaces	Max. Internal HDDs	3 x 3.5" hard disk drawer (1 x 4TB Hard disk included)
Interfaces 1 x Gigabite network port, R145 interface		Max. 24TB (up to 8TB/each)
The continuation	RAID	RAID 1
Audio Out Build-in speaker Point lock 1 x Point lock (Unlock all devices at the same time bye key) "1 x USB 2.0: for extended device USB 2 x Mini USB: for thirdparty device charging Deparating Temperature 2 x Micro USB: for thirdparty device charging Operating Humidity 1.0°C ~ 55°C / 14°F ~ 131°F Electrical 100% ~ 95% Power 100 ~ 240V AC, 50 ~ 60Hz "2CS-KDCA1-6: Max. 105W ZCS-KDCA1-6+1 x ZCS-KDCA1-EX6: Max. 135W ZCS-KDCA1-6+2 x ZCS-KDCA1-EX6: Max. 165W ZCS-KDCA1-6+3 x ZCS-KDCA1-EX6: Max. 195W Power-Off Protection Built-in battery: 2150mAh Mechanical Weight ZCS-KDCA1-EX6: 3.68Kg/8.11lb Dimensions ZCS-KDCA1-6: 40 x ZS-KDCA1-6: 40 x SS-KDCA1-6:	Interfaces	
Audio Out	Ethernet	1 x Gigabite network port, RJ45 interface
Point lock	Audio Out	
"1 x USB 2.0: for extended device		
2 x Mini USB: for thirdparty device charging 2 x Micro USB: for thirdparty	1 onte toere	
2 x Micro USB: for thirdparty device charging	LICD	
10°C ~ 55°C / 14°F ~ 131°F	USB	
Operating Temperature Operating Humidity -10°C ~ 55°C / 14°F ~ 131°F Operating Humidity 10% ~ 95% Electrical Power 100 ~ 240V AC, 50 ~ 60Hz Power Consumption 2CS-KDCA1-6: Max. 105W Power Consumption 2CS-KDCA1-6+1 x ZCS-KDCA1-EX6: Max. 135W Power-Off Protection Mechanical Weight 2CS-KDCA1-6+3 x ZCS-KDCA1-EX6: Max. 195W Built-in battery: 2150mA1 2 CS-KDCA1-6: 10.3 Kg / 22.71b (HDD not included) Dimensions ZCS-KDCA1-6: 430 x 510 x 98mm / 16.92" x 20.08" x 3.86"		2 x Micro USB: for thirdparty device charging
Operating Humidity 10% ~ 95% Electrical 100 ~ 240V AC, 50 ~ 60Hz Power "2CS-KDCA1-6: Max. 105W ZCS-KDCA1-6 + 1 x ZCS-KDCA1-EX6: Max. 135W ZCS-KDCA1-6 + 2 x ZCS-KDCA1-EX6: Max. 135W ZCS-KDCA1-6 + 3 x ZCS-KDCA1-EX6: Max. 165W ZCS-KDCA1-6 + 3 x ZCS-KDCA1-EX6: Max. 195W Power-Off Protection Mechanical Weight ZCS-KDCA1-6: 10.3 Kg / 22.7 lb (HDD not included) Weight ZCS-KDCA1-EX6: 3.68Kg/8.11B Dimensions ZCS-KDCA1-6: 430 x 510 x 98mm / 16.92" x 20.08" x 3.86"		14000 5500 14405 40405
Electrical		
Power 100 ~ 240V AC, 50 ~ 60Hz "ZCS-KDCA1-6: Max. 105W Power Consumption ZCS-KDCA1-6 + 1 x ZCS-KDCA1-EX6: Max. 135W Power-Off Protection ZCS-KDCA1-6 + 2 x ZCS-KDCA1-EX6: Max. 165W Mechanical Built-in battery: 2150mAh Weight ZCS-KDCA1-6: 1 0 . 3 Kg / 2 2 . 7 lb (HDD not included) ZCS-KDCA1-EX6: 3.68Kg/8.11B Dimensions ZCS-KDCA1-6: 43 0 x 5 10 x 98mm / 16.92" x 20.08" x 3.86"		10% ~ 95%
TZCS-KDCA1-6: Max. 105W ZCS-KDCA1-6+ 1 x ZCS-KDCA1-EX6: Max. 135W ZCS-KDCA1-6+ 1 x ZCS-KDCA1-EX6: Max. 135W ZCS-KDCA1-6+ 2 x ZCS-KDCA1-EX6: Max. 165W ZCS-KDCA1-6+ 3 x ZCS-KDCA1-EX6: Max. 195W Built-in battery: Z15mAt Built-in battery: Z15mAt ZCS-KDCA1-EX6: 3.68Kg/8.11B ZCS-KDCA1-EX6: 3.68Kg/8.31B ZCS-KDCA1-6: 430 x 510 x 98mm / 16.92" x 20.08" x 3.86" ZCS-KDCA1-6: 430 x 510 x 98mm / 16.92" x 20.08" x 3.80" ZCS-KDCA1-6: 430 x 510 x 98mm / 16.92" x 20.08" x 3.80" ZCS-KDCA1-6: 430 x 510 x 98mm / 16.92" x 20.08" x 3.80" ZCS-KDCA1-6: 430 x 510 x 98mm / 16.92" x 20.08" x 3.80" ZCS-KDCA1-6: 430 x 3.80"		
Power Consumption ZCS-KDCA1-6 + 1 x ZCS-KDCA1-EX6: Max. 135W ZCS-KDCA1-6 + 2 x ZCS-KDCA1-EX6: Max. 165W ZCS-KDCA1-6 + 3 x ZCS-KDCA1-EX6: Max. 195W Power-Off Protection Mechanical Weight Built-in battery: 2150mAh Weight Z CS-KDCA1-EX6: 10. 3 Kg / 2 2.7 lb (HDD not included) ZCS-KDCA1-EX6: 3.68Kg/8.11lb Dimensions Z CS-KDCA1-6: 430 x 510 x 98mm / 16.92" x 20.08" x 3.86"	Power	
ZCS-KDCAL-6 + 2 x ZCS-KDCAL-EK6: Max. 165W ZCS-KDCAL-6 + 3 x ZCS-KDCAL-EK6: Max. 195W		"ZCS-KDCA1-6: Max. 105W
Dimensions Dimensions Dimensions Dimensions Dimensions Dimensions Dimensions Dimensions Dimensions Dimensions Dimensions Dimensions Dimensions Dimensions Dimensions Dimensions Dimensions Dimensions	Power Consumption	ZCS-KDCA1-6 + 1 x ZCS-KDCA1-EX6: Max. 135W
CS-KDCA1-6+3x ZCS-KDCA1-EX6: Max. 195W		
Power-Off Protection Built-in battery: 2150mAh Mechanical		
Mechanical ZCS-KDCA1-6: 10.3 Kg / 22.7 lb (HDD not included) Weight ZCS-KDCA1-EX6: 3.68Kg/8.11lb Dimensions ZCS-KDCA1-6: 430 x 510 x 98mm / 16.92" x 20.08" x 3.86"	Davies Off Duetesties	
Weight ZCS-KDCA1-6: 10.3 Kg / 22.7 lb (HDD not included) ZCS-KDCA1-EX6: 3.68Kg/8.11lb Dimensions ZCS-KDCA1-6: 430 x 510 x 98mm / 16.92" x 20.08" x 3.86"		Dulicili Dattery. 2130IIIAII
ZCS-KDCA1-EX6: 3.68Kg/8.11lb Dimensions		7.00 KD044 6: 40 2K- / 22 7H- /HDD+ (1::4-4)
Dimensions ZCS-KDCA1-6: 430 x 510 x 98mm / 16.92" x 20.08" x 3.86"	vveignt	
		ZCS-KDCA1-EX6: 3.68Kg/8.11lb
ZCS-KDCA1-EX6: 190 x 510 x 98mm / 7.48" x 20.08" x 3.86"	Dimensions	
		ZCS-KDCA1-EX6: 190 x 510 x 98mm / 7.48" x 20.08" x 3.86"

Units:mm Dimensions -----



